

Technical Data Sheet

CP-70 (Cyclopentane/Isopentane Blend - 70:30)

Sale Specification			
Item	Specification	Test Method	Units
Cyclopentane	67.00 – 73.00	Gas Chromatograph	wt. %
Isopentane	27.00 – 33.00	Gas Chromatograph	wt. %
Normal Pentane	5.0 maximum	Gas Chromatograph	wt. %
C4 & Lighter	0.50 maximum	Gas Chromatograph	wt. %
Benzene	5.0 maximum	Gas Chromatograph	wt. ppm
n-Hexane	20.0 maximum	Gas Chromatograph	wt. ppm
Water	100.0 maximum	ASTM D-1364	wt. ppm
Appearance	Clear	ASTM D-329	--
Technical Data			
Parameter	Conditions	Units	Value
Boiling Range	-	C	28-49
Vapor Pressure	20 C	kPa	35-77
Flash Point	-	C	-51- -29

1.11.2021

OTHER INFORMATION

Shipping: Shipped in ISO containers; 13,500 kg and 17,000 kg minimum order; Korean Product
DOT Classification: UN 1265, 70/30 Cyclopentane/Isopentane, Class 3, PG II

Matt Scott
Performance Chemicals Sales Manager
T [+1] 567-288-5448
matt.scott@agas.com

A-Gas
1100 Haskins Road
Bowling Green
Ohio 43402, USA
T [+1] 419-867-8990

Jacob Young
Logistics Coordinator
T [+1] 419-867-8990
jacob.young@agas.com