

# Technical Data Sheet

CP-80 (Cyclopentane/Isopentane Blend - 80:20)

Sale Specification			
Item	Specification	Test Method	Units
Cyclopentane	77.00 – 83.00	Gas Chromatograph	wt. %
Isopentane	17.00 – 23.00	Gas Chromatograph	wt. %
Normal Pentane	5.0 maximum	Gas Chromatograph	wt. %
C4 & Lighter	0.50 maximum	Gas Chromatograph	wt. %
Benzene	5.0 maximum	Gas Chromatograph	wt. ppm
n-Hexane	20.0 maximum	Gas Chromatograph	wt. ppm
Water	100.0 maximum	ASTM D-1364	wt. ppm
Appearance	Clear	ASTM D-329	--
Technical Data			
Parameter	Conditions	Units	Value
Boiling Range	-	C	28-49
Vapor Pressure	20 C	kPa	35-77
Flash Point	-	C	-57- -42

1.1.2021

## OTHER INFORMATION

Shipping: Shipped in ISO containers; 13,500 kg and 17,000 kg minimum order; Korean Product  
DOT Classification: UN 1265, 80/20 Cyclopentane/Isopentane, Class 3, PG II

**Matt Scott**  
Performance Chemicals Sales Manager  
T [+1] 567-288-5448  
matt.scott@agas.com

**A-Gas**  
1100 Haskins Road  
Bowling Green  
Ohio 43402, USA  
T [+1] 419-867-8990

**Jacob Young**  
Logistics Coordinator  
T [+1] 419-867-8990  
jacob.young@agas.com