

## MAXIMUM CYLINDER RECOVERY WEIGHTS FOR RECOVERY/TRANSPORT (80% FILL)

### MAXIMUM NET RECOVERY WEIGHTS

DOT 4BA / 4BW / 106A / 110A CYLINDERS

		Min. Service PSI	30#	50#	100#	125#	240#	500#	1000#	2000#
CFC	Mixed Refrigerants	400	22	40	80	104	202	401	851	1420
	R11	—	31	56	111	145	283	561	1188	1984
	R12	240	28	50	100	129	253	502	1063	1775
	R113	—	33	59	117	152	298	591	1252	2090
	R115	—	32	58	116	151	294	584	1237	2065
HCFC	R22	240	25	45	90	117	230	455	965	1611
	R123	240	31	55	110	143	280	556	1179	1967
	R401A	240	25	45	90	116	227	451	956	1596
	R409A	240	26	46	91	119	232	460	975	1628
	R125	400	25	45	89	116	226	449	952	1589
	R134A	240	26	46	91	119	232	461	977	1630
	R227EA	240	29	52	104	135	264	523	1109	1851
	R404A	300	22	40	80	104	202	401	851	1420
	R407A	300	24	44	87	113	221	439	930	1553
	R407C	300	24	43	87	113	221	438	928	1549
HFC	R407F	400	23	42	84	109	213	422	894	1492
	R410A	400	23	41	81	106	206	410	868	1449
	R417A	240	25	45	90	117	228	453	960	1603
	R421A	260	31	55	109	142	278	552	1169	1951
	R422D	260	24	43	85	111	216	429	909	1517
	R507	300	22	40	80	104	203	403	854	1426
	R448A	300	23	41	82	106	208	412	874	1459
	R449A	300	23	42	83	108	212	420	891	1487
	R453A (RS44B)	240	24	43	85	111	217	430	911	1520