

Technical Data Sheet

CP-85 (Cyclopentane/Isopentane Blend - 85:15)

Sale Specification			
Item	Specification	Test Method	Units
Cyclopentane	82.00 – 88.00	Gas Chromatograph	wt. %
Isopentane	12.00 – 18.00	Gas Chromatograph	wt. %
Normal Pentane	5.0 maximum	Gas Chromatograph	wt. %
C4 & Lighter	0.50 maximum	Gas Chromatograph	wt. %
Benzene	5.0 maximum	Gas Chromatograph	wt. ppm
n-Hexane	20.0 maximum	Gas Chromatograph	wt. ppm
Water	100.0 maximum	ASTM D-1364	wt. ppm
Appearance	Clear	ASTM D-329	--

Technical Data			
Parameter	Conditions	Units	Value
Boiling Range	-	C	28-49
Vapor Pressure	20 C	kPa	35-77
Flash Point	-	C	-57- -42

1.11.2021

OTHER INFORMATION

Shipping: Shipped in ISO containers; 13,500 kg and 17,000 kg minimum order; Korean Product
DOT Classification: UN 1265, 85/15 Cyclopentane/Isopentane, Class 3, PG II

Matt Scott
Performance Chemicals Sales Manager
T [+1] 567-288-5448
matt.scott@agas.com

A-Gas
1100 Haskins Road
Bowling Green
Ohio 43402, USA
T [+1] 419-867-8990

Jacob Young
Logistics Coordinator
T [+1] 419-867-8990
jacob.young@agas.com